





REMOVING POST FROM WATERLINE on The Drinking Post Waterer

Materials needed to complete this repair:

- PVC Teflon Paste
- Piece of 2" x 4" wood cut between 5 1/2" to 6" in length
- Phillips head screwdriver

1. Turn your water supply line off.
2. Remove the paddle from the bowl.
3. Place a 'handle' between the bowl hinges. (Typically a 5 1/2" to 6" length of a piece of 2 x 4 wood)



4. Turn the bowl counter clockwise to release it from the supply line. Depending on how tight the post is connected to your waterline, this may take some muscles. Once completely unscrewed from waterline, pull the Drinking Post up carefully through the guide in the base of the 8" support pipe.
5. Once you have the post disconnected from your water line and removed from the ground, you may wish to relocate to a 'workshop' area.
6. AFTER PERFORMING MAINTENANCE, TO REINSTALL, FOLLOW BELOW
7. Apply some PVC Teflon paste to the base threads if needed to help lubricate the connection and prevent leaks.
8. Insert the Post into the 8" pipe and carefully turn the Post clockwise until gently securing it on the supply line. Be careful not to cross thread your connection. Hand-tighten using the 2 x 4 method mentioned above.
9. Reattach the paddle.
10. Turn on your supply line water.