



FENCE PRO BLACK

ACRYLIC LATEX FENCE & BARN PAINT

Product Description:

A 100% acrylic paint formulated especially for wood plank fences. This product offers exceptional economy and durability in a user friendly water based formulation. Provides excellent weather protection and decoration, and is safe around valuable livestock. Can be applied directly to new, weathered or previously painted lumber with the convenience of soap and water clean up. Other applications include barns, sheds and other farm structures.

Performance Information:

- * 100% acrylic latex formulation
- * Self-priming
- * Low odor
- * Fast dry time
- * Excellent weather protection
- * Safe around valuable live stock
- * Easy soap and water clean-up
- * Environmentally safe alternative to solvent based products.

Uses:

- * Plank Fences
- * Barns
- * Run In Sheds
- * Farm Buildings

Characteristics:

- * Color - Black
- * Finish - Satin, 20 to 30 units at 60 degrees
- * Drying time - @ 77F and 50% relative humidity
To touch: 30 min.
Re-coat : 4 hours
- * Flash point - above 201F (PMCC)
- * Viscosity - 88KU
- * Recommended coverage rate:
3 & 4 board plank fence - 16 running feet per gallon (both sides)
1 board plank fence - 26 running feet per gallon (both sides)
Barns - 325 square feet per gallon on smooth surfaces
Less than recommended applications will see a marked difference in durability.
- * Shelf life - 2 years (unopened, proper agitation)
- * Package - 5 gal pails, 55 gal drums
- * VOC - less than 250 grams/liter

Application:

- * Apply to clean dry fence with brush, roller or spray
- * Airless spray requirements:
Rating - 0.5 gallons per minute minimum
Pressure - 1800 to 2500psi
Filter - 30 to 60 mesh
Tip - .017" to .021"
- * Apply at full body
- * Stir thoroughly before applying
- * Fence preparation - For greatest durability make sure fence is scraped thoroughly by removing any peeling or flaking paint before applying.
- * Allow new wood 1 to 3 month to weather in order to reduce moisture content.
- * Application temperature - Above 50F(30C)
- * Follow recommended coverage rate for best results.
- * Storage - **DO NOT FREEZE**
- * Clean up with soap and water