



# Wash Stall Wand

## Assembly & Installation Instructions



**System Equine**

14321 Fifth Line Nassagaweya • Rockwood, ON • NOB 2K0

1 (800) 461-3362 • Sales@SystemEquine.com

SystemEquine.com

# TOOLS REQUIRED



- 1 small pipe wrench
- 7/8 open end wrench
- 7/16 socket and driver

1. Verify all the parts are there.



2. Decide whether it is wall mount or ceiling mount.



3. Place provided 5/8 washer over threaded end on water swivel, put through hole in bracket, placing other washer and supplied 3/8 to 1/2 reducer. Be sure to tighten firmly.



- Using supplied lags, fix bracket and swivel to wall where you wish it to be.



- Locate swivel pipe, 3/8 nipple and other 3/8 to 1/2 reducer and 90 degree elbow.
- Thread reducer to pipe, thread nipple to reducer and lastly thread 90 degree elbow to other end.



- Using pipe wrench, tighten swivel pipes reduced end (with nipple) into water swivel.
- Tighten 90 degree elbow so it points to the ground.



- Screw provided hose into elbow, attach hose sprayer. Connect water supply (from barn) into 3/8 to 1/2 reducer inside the swivel mount box. Your wash stall sprayer is now ready for use.

